

CLAIMS

What is claimed is:

1. Method for encoding an input pattern using a normalizer and a classifier during the learning phase, said input pattern being characterized by an essential feature or shape and at least one main parameter wherein said main parameter is an element susceptible of modifying the input pattern but not the shape, comprising the steps of:

establishing a reference value for that main parameter;

applying said input pattern to a normalizer that computes a main factor which measures the difference between the main parameter value of said input pattern and said reference value and that sets the input pattern at said reference value as a normalized pattern using said main factor;

applying said normalized pattern and the category associated thereto by the user to a classifier; and,

storing the normalized pattern in the classifier as a prototype;

wherein said normalized pattern, said category and main factor represent the encoded pattern.

2. The method of claim 1 wherein said at least one main parameter is a mean value and said main factor consists of an offset used to shift the input pattern to said reference value.

3. The method of claim 1 wherein said at least one main parameter is the orientation of the input pattern and said main factor consists of a angle value used to rotate the input pattern to said reference value.

5 4. The method of claim 1 wherein said at least one main parameter is the amplitude of the input pattern and said main factor consists of a gain used to modify the input pattern to said reference value.

10 5. The method of claim 1 wherein said classifier is an input space mapping algorithm based artificial neural network (ANN).

6. The method of claim 5 wherein said ANN comprises at least one ZISC neuron.

15 7. Method for encoding a new (unknown) input pattern using a normalizer and a classifier during the classification phase, said new input pattern being characterized by an essential feature or shape and at least one main parameter wherein said main parameter is an element susceptible of modifying the new input pattern but not the shape,
20 comprising the steps of:

establishing a reference value for that main parameter;

applying said new input pattern to a normalizer that computes a main factor which measures the difference between the main parameter value of said new input pattern

and said reference value and that sets the input pattern at said reference value as a normalized pattern using said main factor; and,

applying said normalized pattern to a classifier having normalized patterns stored therein as prototypes to generate the category.

8. The method of claim 7 wherein said at least one main parameter is of a mean value and said main factor consists of an offset used to shift the input pattern to said reference value.

9. The method of claim 7 wherein said at least one main parameter is the orientation of the input pattern and said main factor consists of a angle value used to rotate the input pattern to said reference value.

10. The method of claim 7 wherein said at least one main parameter is the amplitude of the input pattern and said main factor consists of a gain used to modify the input pattern to said reference value.

11. The method of claim 7 wherein said classifier is an input space mapping algorithm based artificial neural network (ANN).

12. The method of claim 11 wherein said ANN comprises at least one ZISC neuron.

13. The method for decoding a new (unknown) input pattern

during the classification phase, said new input pattern being characterized by an essential feature or shape and at least one main parameter wherein said main parameter is an element susceptible of modifying the new input pattern but not the shape, comprising the steps of:

establishing a reference value for that main parameter;

applying said new input pattern to a normalizer that computes a main factor which measures the difference between the main parameter value of said new input pattern and said reference value and that sets the input pattern at said reference value as a normalized pattern using said main factor;

applying said normalized pattern to a classifier having normalized patterns stored therein as prototypes to generate the category wherein said prototypes represent the codebook memory of the classifier and wherein said category and main factor are the identification data of said new input pattern;

applying said category to said codebook memory to extract the normalized pattern corresponding thereto; and,

applying said normalized pattern and the main factor to a denormalizer to retrieve a pattern close to said new input pattern.

14. The method of claim 13 wherein said at least one main parameter is of a mean value and said main factor consists of an offset used to shift the input pattern to said reference value.

15. The method of claim 13 wherein said at least one main parameter is the orientation of the input pattern and said main factor consists of a angle value used to rotate the input pattern to said reference value.

5 16. The method of claim 13 wherein said at least one main parameter is the amplitude of the input pattern and said main factor consists of a gain used to modify the input pattern to said reference value.

10 17. The method of claim 13 wherein said classifier is an input space mapping algorithm based artificial neural network (ANN).

18. The method of claim 17 wherein said ANN comprises at least one ZISC neuron.

15 19. A system for encoding an input pattern, said input pattern being characterized by an essential feature or shape and at least one main parameter wherein said main parameter is an element susceptible of modifying the input pattern but not the shape, comprising:

20 means for applying the input pattern to a normalizer;
means for applying a category to an ANN;
a normalizer having a reference value for that parameter stored therein that computes a main factor which measures the difference between the main parameter value of said input pattern and a reference value thereof and that sets
25 the input pattern at said reference value as a normalized

pattern using said main factor; and,

an ANN adapted to receive said normalized pattern and to store the normalized pattern in a neuron of the ANN as a prototype with the category associated thereto;

5 wherein said normalized pattern, said category and main factor represent the encoded pattern.

20. An identification system for encoding a new (unknown) input pattern, said input pattern being characterized by an essential feature or shape and at least one main parameter wherein said main parameter is an element susceptible of modifying the input pattern but not the shape, comprising:

means for applying the new input pattern to a normalizer; a normalizer having a reference value for that parameter stored therein that computes a main factor which measures the difference between the main parameter value of said new input pattern and a reference value thereof and that sets the new input pattern at said reference value as a normalized pattern using said main factor; and,

a classifier storing the normalized patterns that have been previously learned in the codebook thereof as prototypes with the category associated thereto adapted to receive said normalized pattern from the normalizer to generate the category of the normalized pattern.

21. A retrieval system adapted to decode an new (unknown) input vector during the classification phase, said input pattern being characterized by an essential feature or shape and at least one main parameter wherein said main

parameter is an element susceptible of modifying the input pattern but not the shape, comprising:

means for applying the new input pattern to a normalizer;
a normalizer having a reference value for that parameter
5 stored therein that computes a main factor which measures the difference between the main parameter value of said new input pattern and a reference value thereof and that sets the new input pattern at said reference value as a normalized pattern using said main factor;

10 a classifier storing the normalized patterns that have been previously learned in the codebook thereof as prototypes with the category associated thereto adapted to receive said normalized pattern from the normalizer to generate the category of the normalized pattern.

15 means for applying the category of the normalized pattern to the codebook memory of the classifier;

means for applying the main factor to a denormalizer;

means for extracting the normalized pattern corresponding to that category from the codebook memory; and,

20 a denormalizer adapted to receive said main factor and said normalized pattern to retrieve a pattern close to the original input pattern.

22. A computer program product comprising:

a computer useable medium having computer readable code

25 means embodied therein for causing a computer to encode an input pattern using a normalizer and a classifier during a learning phase, the input pattern

having an essential feature or shape and at least one main parameter that is an element susceptible of modifying the input pattern but not the shape, the computer readable code means in the computer program product comprising:

computer readable program code means for causing a computer to establish a reference value for the main parameter;

computer readable program code means for causing a computer to apply the input pattern to a normalizer that computes a main factor that measures the difference between the main parameter value of the input pattern and the reference value and that sets the input pattern at the reference value as a normalized pattern using the main factor;

computer readable program code means for causing a computer to apply the normalized pattern and the category associated thereto by the user to a classifier; and

computer readable program code means for causing a computer to store the normalized pattern in the classifier as a

prototype, wherein the normalized pattern the category and main factor represent the encoded pattern.

23. An article of manufacture comprising:

5 a computer useable medium having computer readable program code means embodied therein for causing a computer to encode a new unknown input pattern using a normalizer and a classifier during a classification phase, the new input pattern having an essential feature or shape and at least one main parameter, wherein the main parameter is an element susceptible of modifying the new input pattern but not the shape, the computer readable code means in the article of manufacture comprising:

10 computer readable program code means for causing a computer to establish a reference value for the main parameter;

15 computer readable program code means for causing a computer to apply the new input pattern to a normalizer that computes a main factor that measures a difference between the main parameter value of the new input pattern and the reference value and that sets the input pattern at the reference value as a

normalized pattern using the main factor; and

computer readable program code means for causing a
computer to apply the normalized pattern to a
classifier having normalized patterns stored therein
as prototypes to generate the category.

5

TOP SECRET